ProLite E2407HDSV-1

The ProLite E2407HDSV features 'true' 16:9 High Definition 1920 x 1080 native resolution. Complimented with a blistering 2msec response rate and a 30,000:1 Advance Contrast Ratio. The E2407HDSV guarantees great performance for Gamers and Multimedia Applications. Finished in a stylish Piano Black design, the E2407HDSV is sure to stand out amongst the crowd!

Panel	TN
Diagonal	24"
Display area h x w	293.2 x 521.3 mm
Response time	2 ms
Contrast	30000 : 1 ACR
Contrast	1000 : 1 typical
Brightness	300 cd/m² typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.2715 x 0.2715 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	31 - 80 KHz
Vertical sync	56 - 75 Hz
Analog input connector	D-Sub
Synchronization	Separate Sync
Plug & Play	VESA DDC 1/2B™
Speakers	2 x 3 W (Stereo)
Included accessories	Power Cable, D-Sub Cable, Audio cable, user manual, stand
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 8 languages (EN, DE, FR, ES, IT, FI, JP, Chinese) and 5 front controls (Menu, Scroll Down/ Brightness/ Contrast/ ACR/ ECO, Scroll Up/ OptiColour, Select, Power)
User controls	auto adjust, contrast, brightness, ACR, ECO, audio adjust (volume, mute), colour adjsut, information, manual image adjust (horizontal size, H/V position, fine tune, sharpness, video mode adjust, OptiColour mode), setup menu (language select, OSD position, OSD time out, OSD background), memory recall
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista
Safety	CE, TUV/Baurt
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	46 W typical; max. 1 W in Power management mode
Power management	ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up
Dimensions w x h x d	560 x 404.5 x 220 mm
Weight	5 kg
Aspect ratio	16 : 9

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.